



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 11 March 2004

**THIS PAGE BLANK (USPTO)**



1/77  
01APR03-E796646-1 D02246  
P01/7700 0.00-0307437.4

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

P014114GB

2. Patent application number

(The Patent Office will fill in this part)

0307437.4

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)

SUN MICROSYSTEMS, INC  
4120 Network Circle  
Santa Clara  
California 95054  
United States of America

Patents ADP number (*if you know it*)

If the applicant is a corporate body, give the country/state of its incorporation

State of Delaware

8454795002

4. Title of the invention

FAN GRILL

5. Name of your agent (*if you have one*)

D Young & Co

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

21 New Fetter Lane  
London  
EC4A 1DA

Patents ADP number (*if you know it*)

59006 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number  
(*if you know it*)

Date of filing  
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(*day / month / year*)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

Yes

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form None

Description 12

Claim(s) 5

Abstract 1

Drawing(s) 4 + 4 RM

10. If you are also filing any of the following, state how many against each item.

Priority documents None

Translations of priority documents None

Statement of inventorship and right to grant of a patent (Patents Form 7/77) None


Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77) 1

Any other documents (please specify) None

11.

I/We request the grant of a patent on the basis of this application.

Signature  26  
D Young & Co (Agents for the Applicants)

Date 31 March 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Ian Harris

023 8071 9500

**Warning**

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 7/77

Patents Act 1977  
(Rule 15)




19MAY03 5132065-4 D02246  
P07/7700 0.00-0307437.4

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

**Statement of inventorship and of  
right to grant of a patent**



1. Your reference	P014114GB
2. Patent application number (if you know it)	0307437.4
3. Full name of the or of each applicant	SUN MICROSYSTEMS, INC
4. Title of the invention	Fan Grill
5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent	By virtue of an Assignment dated 31 March 2003
6. How many, if any, additional Patents Forms 7/77 are attached to this form? (see note (c))	None
7.	<p>I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.</p> <p>Signature  Date 15 May 2003</p> <p>D Young &amp; Co (Agents for the Applicants)</p>
8. Name and daytime telephone number of person to contact in the United Kingdom	Ian Harris 023 8071 9500

**Notes**

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

**Patents Form 7/77**

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Surname: <u>GARNETT</u>	
First Names: Paul Jeffrey	
Little Orchard	
Knightsbridge Road	
Camberley	
Surrey GU15 3TS	
United Kingdom	
8524027001	
Patents ADP number (if you know it):	

Surname: _____	
First Names: _____	
Patents ADP number (if you know it):	

Surname: _____	
First Names: _____	
Patents ADP number (if you know it):	

**Reminder**

**Have you signed the form?**

FAN GRILL

## BACKGROUND OF THE INVENTION

5

The invention relates to fan grills for covering fans or openings in fan housings.

The invention finds particular but not exclusive use in electrical equipment, such as computer systems, which may comprise field replaceable units (FRUs).

Fans are generally provided in electrical equipment such as computer equipment in order to provide cooling for the electrical components thereof. Typically, a fan is mounted inside an enclosure containing the electrical components and an aperture is provided in the chassis defining the enclosure so that hot air may be expelled.

In general, it is desirable to provide grills for fans that provide some level of protection from moving fan blades while presenting minimal restriction to the flow of air in the vicinity of the fan.

Fans have a propensity to collect dirt from the surrounding environment, which can increase the chance of failure and also degrade performance by restricting airflow.

Since fans are electromechanical devices comprising moving parts, they are more likely fail (and hence require replacement/maintenance) than, for example, purely electrical components.

It is generally desirable that the removal and/or replacement of a fan unit be easily and swiftly effected. It is also desirable that removal and/or replacement of the grill from the fan or fan unit itself be easily and swiftly effected.

These considerations are of particular relevance in electrical equipment comprising FRUs wherein there is an emphasis on minimising downtime in the event of a fault.

30

Accordingly, there is a need for a grill which is easily and removably mountable on a fan or a housing, which facilitates removal of the fan or a fan unit from the system in which it is incorporated.



## SUMMARY OF THE INVENTION

In accordance with one aspect of the invention, there is provided a grill configured to be mounted on a fan or a housing. The grill comprises a substantially planar portion and a handle extending out of the planar portion.

The substantially planar portion of the grill provides protection for the blades of a fan while the provision of a handle facilitates mounting and removal of the grill from a fan or fan housing. Furthermore, the handle also provides means by which the fan or fan unit as a whole may be mounted or removed from equipment into which it is incorporated.

The substantially planar portion may be provided with a plurality of apertures. These apertures can facilitate airflow through the grill and reduce the weight of the grill. The apertures can be arranged in a grid. The substantially planar portion may comprise at least one shaped wire arranged to form a loop or partial loop. A number of such loops or partial loops may be provided. These loops or partial loops provide protection for the fan blades while apertures between them allow air to flow through the grill. To strengthen the grill, a number of struts may be provided. Each strut can be attached to one or more of the loops or partial loops thereby providing them with support.

Various embodiments of the invention may comprise an opening in the substantially planar portion arranged to receive the handle of a second grill. In this manner, a number of grills may be stacked together, with the handle of each grill passing through the opening in substantially planar portion of (at least) the next grill in the stack. Such an arrangement can be efficient in terms of packaging since both space and packaging materials are saved.

The handle portion may comprise a piece of wire extending in a loop or partial loop away from the planar portion. This construction can present a minimal obstruction to airflow and economies with regard to the use of materials. Additional pieces of wire may be provided to strengthen the handle.

The grill may be provided with mounting formations for mounting the grill to a fan or fan housing. The mounting formations may comprise shaped wire extending away from the planar portion and arranged to form a loop or partial loop.

One or more of the features of the grill may be integrally formed from a single piece of shaped wire. Construction of the grill may thus be simplified, the number of joins using welds or other jointing techniques may be reduced and the strength of the grill may be increased. Examples of such embodiments include: a grill in which at least one mounting formation and a portion of the handle are integrally formed from a single piece of shaped wire, a grill in which at least one strut and at least a portion of the handle are integrally formed from a single piece of shaped wire, a grill in which at least one mounting formation and strut are integrally formed from a piece of shaped wire and a grill in which at least one mounting formation, strut and at least a portion of the handle are integrally formed from a single piece of shaped wire.

In accordance with another aspect of the invention, there is provided a combined fan grill and handle comprising: a section of wire shaped to form at least one loop or partial loop arranged in a common plane, including an outermost loop or partial loop; a section of wire shaped to provide support for each loop or partial loop; a first section of wire shaped to form a handle portion; and at least one mount.

In accordance with yet another aspect of the invention there is provided a method for a covering for an opening in an enclosure, the enclosure at least partially enclosing a fan. The method includes providing a grill comprising a substantially planar portion, and a handle extending out of the planar portion.

## BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the present invention will be described hereinafter, by way of example only, with reference to the accompanying drawings in which like reference  
5 signs relate to like elements and in which:

Figure 1A shows a fan grill in accordance with an embodiment of the present invention;

Figure 1B shows a side view of the fan grill shown in Figure 1A;

Figure 2A shows a fan grill in accordance with an embodiment of the present  
10 invention;

Figure 2B shows a side view of the fan grill shown in Figure 2A;

Figure 3A shows a fan grill in accordance with an embodiment of the present invention;

Figure 3B shows a side view of two of the grills shown in Figure 3A stacked  
15 together;

Figure 3C shows a side view of several of the grills shown in Figure 3A stacked together – for clarity, the outermost loop of each grill is not shown in this Figure;

Figure 4 shows an alternative embodiment of the handle of a fan grill in  
20 accordance with an embodiment of the present invention;

Figure 5 shows an alternative embodiment of the handle of a fan grill in accordance with an embodiment of the present invention; and

Figure 6 is a schematic representation of a fan module with a fan grill.

## DESCRIPTION OF PARTICULAR EMBODIMENTS

Various embodiments of the invention are described hereinafter by way of example only.

5       The various examples of grills 10 described herein include a substantially planar portion 90, which provides protection for (or indeed protection from) the blades of a fan, and also a handle 100 that serves to facilitate mounting of the grill 10 on a fan or on a housing. When the grill 10 is mounted on a fan or a housing, for example a fan housing, the handle 100 also provides a means by which both the grill 10 and fan or fan housing may be lifted or carried as a single item.

One approach that may be taken in providing a grill 10 in accordance with the present invention is to use a wire or wire like construction. Examples of suitable materials for the wire include, for example, metal, or plastics or a combination thereof. Typically a metal is used for reasons of strength and heat and fire resistance.

15 For example, metal wire may be bent or shaped to form a variety of features comprising the grill 10. When plastics are used, construction of the grill 10 may comprise a molding process such as injection molding. In such cases, the end result would be a wire-like construction for the grill although no actual wire is used in the grills construction as such. Accordingly, as used herein, the term 'wire' refers both

20 wire and wire-like features.

The thickness of the wire may vary, but for most applications wire of diameter 1.6mm (American Wire Gauge (AWG) 14) should prove to be adequate. It is noted that wire that is unnecessarily thick only presents a greater barrier to airflow without significant benefit being accrued in terms of the strength or durability of the grill 10

25 itself. The choice of wire thickness can be based upon the size of the intended grill 10 and on the type of wire being used, as will be apparent to one skilled in the art.

It is envisaged that wire of various cross sectional shapes could be employed, examples being wires with circular, square or triangular cross sections.

In choosing construction materials for the grill 10, it is not necessary that only a single material or type of wire be employed. For example, a first type of wire may be used to construct the substantially planar portion 90 while a second, different type of wire may be used to form the handle 100. Nevertheless, in a number of  
5 embodiments it will be preferable to use only wire of a single type whereby the construction process is simplified and the number of joins or welds used in the grill 10 may be reduced.

Also, although in the present examples a wire like construction is used for the various parts of the grill and handle, in other examples parts of the grill and/or the  
10 handle may be formed from a single piece of material. For example, the substantially planar portion and/or the handle may be stamped or otherwise formed from a single piece of sheet material, for example sheet metal.

Turning now to Figure 1A, there is shown a perspective view of an example of a grill 10 in accordance with an embodiment of the present invention.

15 A substantially planar portion 90 of the grill 10 comprises four loops 20, 22, 24 and 30 including an outermost loop 30 and two struts 26 and 28. The handle 100 extends out of the substantially planar portion 90 whereby means for holding/manoeuvring the grill are provided. In this embodiment, the grill also comprises four mounting formations 12, 14, 16 and 18. Each mounting formation is  
20 configured to facilitate mounting of the grill 10 to corresponding mounting features 13 on a fan or fan housing.

In the present example the loops 20, 22, 24 and 30 are substantially circular in shape and are arranged concentrically. It is envisaged that in other embodiments, non-circular arrangements could be employed such as square, rectangular or ellipse-shaped  
25 loops. It is also envisaged that non-concentric arrangements would be possible. For example, the shape of the loops could be matched to the shape of an aperture over which the grill is to be mounted. Furthermore, it will be appreciated that more than one shape of loop could be employed in a single embodiment, one example only of which being shown in Figure 3A.

As shown in Figure 1A, the strut 28 can lie across each of the loops 20, 22, 24 and 30 and pass through the centre of the substantially planar portion 90. The strut 28 can be attached to each of the loops 20, 22, 24 and 30 in two places with the attachments 92 indicated. Each of the attachments 92 may comprise a weld or  
5 brazing, or some form of adhesive. In the case of a molded grill, a grill stamped from an integral piece of material, or the like, the attachments 92 may not be required as the substantially planar portion may be formed from a single piece on which all the features indicated in Figure 1A are integrally formed. These considerations also apply to the attachments used in other parts of the grill 10, and indeed to the other  
10 embodiments described herein.

The strut 26 can be arranged perpendicular to strut 28 and can lie across each of the loops 20, 22 and 24, for example. The strut 26 can also pass through the centre of the substantially planar portion. Further attachments 92 are provided to attach strut 26 to loops 20, 22 and 24. In this manner it can be seen that the struts 26 and 28 can  
15 provide support for the loops 20, 22, 24 and 30 while also providing additional protection for the fan blades. By providing more struts of the kind described here, the size of the apertures provided within the substantially planar portion may be reduced and the grill may be strengthened, which both afford extra protection for the fan. However, this occurs at a cost of inhibiting the flow of air through the grill. Similar  
20 considerations apply to the loops (or partial loops) and the number thereof that are provided.

In Figure 1B, which shows a side view of the fan grill 10, it can be seen that in this example the strut 26 lies on top of each of the loops 20, 22 and 24. As shown, the strut 28 passes over the top of the strut 26 and also lies on top of loops 20, 22, 24 and  
25 30. In alternative embodiments, each of the struts may for instance be arranged such that they are interwoven with the loops provided or in any other appropriate configuration.

The handle 100 in this example comprises a piece of wire 32, shaped so as to form a partial loop, the ends of which are attached 92 to outermost loop 30. The

handle is arranged so that (when viewed from above the plane of the substantially planar portion) it runs substantially parallel to the strut 26 and perpendicular to the strut 28.

Each of the mounting formations 12, 14, 16 and 18 can comprise a piece of wire with a first portion which extends linearly away from the substantially planar portion and a second portion which is shaped to form a partial loop.

In the embodiment shown in Figures 1A and 1B, each of the mounting formations can be integrally formed with one of the other features of the grill. The mounting formations 12 and 14 and the strut 28 can be formed from a single piece of wire. The mounting formations 16 and 18 and the handle 100 can also be formed from a single piece of wire 32. As described above, this arrangement simplifies the construction of the grill.

The forming more than one feature from a single piece of wire is further illustrated in the embodiment of the invention shown in Figures 2A and 2B. Here the substantially planar portion 90 comprises three loops 34, 36 and 38 and a single strut 40. The grill further comprises a handle and two mounting formations 42 and 44. The handle in this example is of itself of similar construction that shown in Figure 1A. However, from Figure 2A it can be seen that the two mounting formations 42 and 44, the handle 100 and the strut 40 are all integrally formed from a common wire 46. The mounting formations formed by the single piece of wire 46 each comprise a loop in the wire 46 for mounting on a fan or fan housing via a corresponding mounting feature thereon.

Turning now to Figure 3A, there is shown a grill 10 that has a substantially planar portion 90 in which an opening 94 is provided. In addition to an outermost ring 48, the substantially planar portion 90 of grill 10 shown in Figure 3A comprises four partial loops 54/56, and 50/52, which are attached to the struts 60 and 62 respectively. The opening 94 is defined by struts 60 and 62 and also by the portions of the outermost ring 48 proximal the mounting formations 68 and 72.

Two further struts 64 and 66 are also provided although, like struts 60 and 62, these do not pass through the centre of the substantially planar portion 90. In an arrangement similar to that described in relation to Figure 1A, mounting formations 70 and 74 are integrally formed from a single piece of wire with struts 64 and 66 respectively. Again, in common with the embodiment of Figure 1A, the handle 100 and two mounting formations 68 and 72 are integrally formed from a single piece of shaped wire 76.

The opening 94 in the substantially planar portion 90 of the grill 10 is provided with the intention that a number of grills 10 such as that described here may be stacked in a space efficient manner. The opening 94 and the handle 100 are arranged such that when two or more grills 10 are stacked together, the handle of each grill 10 can pass through the opening of the next grill 10 in the stack. This arrangement is shown in Figure 3B. Depending upon the dimensions thereof, each handle 100 may in fact pass through the openings of a number of grills 10 when more than two grills are stacked together. This is illustrated in Figure 3C, which shows a stack of several grills 10. In Figure 3C, the substantially planar portion 90 of each grill 10 has been omitted for clarity of the diagram. From Figures 3B and 3C it can be appreciated that the provision of the opening 94 affords significant savings in terms of packaging space and materials when a number of grills 10 are shipped together.

Figure 4 shows an alternative construction for handle 100. The handle 100 comprises three pieces of wire 97, 98 and 99. A first piece 98 is arranged similarly to the piece of wire comprising the handles shown in Figures 1A and 2A (integers 32 and 76 respectively). To provide additional strength however, two additional pieces of wire 97 and 99 are used. These are arranged to run substantially parallel to the first piece 98 and a number of attachments 92 such as welds may be used to secure the respective pieces of wire together. Also shown in Figure 4 are three separate cross sections of the handle 100, at different positions. While in this embodiment, two additional pieces of wire 97 and 99 have been used, it is envisaged that only one or even more than two additional pieces could be used.



Figure 5 shows a further type of handle. Here the handle comprises a first piece of wire 80 that is arranged similarly to the handle shown in Figure 2A. As in the embodiment shown in Figure 4 however, two additional pieces of wire 81 and 82 have been added. These are attached to the first wire 80 using a number of attachments 92.

5 Figure 5 also shows the cross section of the handle 100 with respect to the strut 83 at three different positions. In these cross sections, wire 80 is shown using filled circles while wires 81 and 82 are shown using the open circles. Proximal the outermost loop 95, two sections of wire 80 (which loops back on itself to form the mounting formations) lie side by side. Distal the outermost ring 95, these two sections diverge  
10 to form strut 83 and part of the handle 100. In each case, wire 81 lies above strut 83 (which comprises a section of wire 80).

In Figures 4 and 5, the details of the construction of the substantially planar portions 90 have been omitted for clarity. It is envisaged that the handles described in Figures 4 and 5 may be incorporated into the embodiments such as those shown in  
15 Figures 1, 2 and 3.

Figure 6 shows a grill 10 mounted on a fan housing 210. As can be seen, the substantially planar portion of the grill 10 covers opening 200 in the fan housing 210, while a handle 100 provides a means by which mounting of the grill may be swiftly effected. It is also evident that, when the grill 10 is mounted on the housing 210, the  
20 handle 100 provides a means by which a fan module, including the fan housing 210 enclosing a fan (not shown) and the grill 10 may be carried as a whole.

As will be appreciated the embodiments of the invention hereinbefore described are provided as illustrative examples and various modifications may be made without departing from the spirit and scope of the present invention.

25 For example, although each of the embodiments have been discussed primarily in terms of a wire construction, it will be appreciated that the these embodiments may also be implemented using for instance a molding or stamping process for form part or all of the grill and handle.

Also, although in the described embodiments each of the components of the substantially planar portion lie within a single plane, it will be appreciated that, for example, at least one of the loops could lie in a different plane or be slightly offset with respect to the other loops. For example, the substantially planar portion could be  
5 slightly domed towards the centre thereof in the direction of the handle. Alternatively, an outer loop could be offset with respect to other loops in a direction opposite to the direction in which the handle extends. In this manner, the outer loops could be mounted to the surface of a fan or a housing with a greater clearance being afforded between the remaining loops and the rotating fan blades that would be the case if all  
10 of the loops were to lie within a single plane. It will be appreciated that similar considerations could be applied where the substantially planar portion is not formed from a series of loops.

Although the embodiments above have been described in considerable detail, numerous variations and modifications will become apparent to those skilled in the art  
15 once the above disclosure is fully appreciated.

CLAIMS

1. A grill configured to be mounted on a fan or fan housing, the grill comprising a substantially planar portion, and a handle extending out of the planar portion.  
5
2. The grill of Claim 1, wherein said substantially planar portion comprises a plurality of apertures.
3. The grill of Claim 2, wherein at least some of said plurality of apertures are  
10 arranged in a grid.
4. The grill of any preceding claim, wherein said planar portion comprises at least one shaped wire arranged to form a loop or partial loop.
- 15 5. The grill of Claim 4, wherein said planar portion comprises a plurality of said loops or partial loops.
6. The grill of Claim 4 or Claim 5, wherein said planar portion comprises at least one strut, each strut attached to at least one loop or partial loop in at least one  
20 place.
7. The grill of any preceding claim, wherein said planar portion comprises an opening arranged to receive the handle of a second grill.
- 25 8. The grill of any preceding claim, wherein the handle comprises a first piece of wire extending in a loop or partial loop away from said planar portion.
9. The grill of Claim 8, wherein said handle comprises at least one additional piece of wire, each additional piece of wire being shaped such that it is

substantially parallel to said first piece of wire over the length of that additional piece of wire.

10. The grill of Claim 9, wherein each additional piece of wire is attached to said first piece of wire with at least one weld or brazing.
11. The grill of any preceding claim, further comprising one or more mounting formations for mounting the grill on a fan or fan housing.
12. The grill of Claim 11, wherein at least one of the mounting formations comprises shaped wire extending away from said planar portion and arranged to form a loop or partial loop.
13. The grill of or Claim 11 or Claim 12, wherein the at least one mounting formation and a portion of said handle are integrally formed from a single piece of shaped wire.
14. The grill of Claim 6, wherein at least one strut and at least a portion of said handle are integrally formed from a single piece of shaped wire.
15. The grill of Claim 6, further comprising at least one mounting formation for mounting the grill on a fan or fan housing, and wherein at least one mounting formation and strut are integrally formed from a piece of shaped wire.
16. The grill of Claim 6, further comprising at least one mounting formation for mounting the grill on a fan or fan housing, and wherein at least one mounting formation and strut and a portion of said handle are integrally formed from a piece of shaped wire.

17. A plurality of grills according to Claim 7 or any claim dependent thereon, arranged such that the handle of a first grill of said plurality extends through said opening in said planar portion of a second grill.
- 5 18. A grill according to Claim 1, wherein the grill comprises:  
a section of wire shaped to form at least one loop or partial loop arranged in a common plane, including an outermost loop or partial loop;  
a section of wire shaped to provide support for each loop or partial loop;  
a first section of wire shaped to form a handle portion; and  
10 at least one mount.
19. The grill of Claim 18, wherein the section of wire forming the handle portion extends away from said common plane, and wherein either end of that section wire is attached to said outermost loop.
- 15 20. The grill of Claim 18 or Claim 19 comprising two mounts formed from shaped wire, said two mounts and said handle portion being formed from a common section of wire.
- 20 21. The grill of any of Claims 18 to 20, wherein said handle portion comprises at least one additional section of wire.
22. The grill of Claim 21, wherein the first section of wire and the additional sections of wire forming said handle portion are joined together with a weld or  
25 a brazing.
23. The grill of any of Claims 18 to 22, wherein a support and a mount are formed from a common section of wire.

24. The grill of any of Claims 18 to 23, comprising further sections of wire shaped to form further loops or partial loops arranged in said common plane.
- 5 25. The grill of any of Claims 18 to 24, comprising further sections of wire arranged to provide further support for the at least one loop or partial loop.
- 10 26. The grill of Claim 25, wherein two of the sections of wire arranged to provide support for the at least one loop or partial loop define an aperture in said fan grill, the aperture being configured to receive the handle of a second, similar fan grill.
- 15 27. An assembly comprising a plurality of grills according to Claim 26, arranged such that the handle of a first grill of said plurality extends through the aperture of a second grill.
- 20 28. A fan assembly comprising a housing having an aperture, a fan mounted within the housing adjacent the aperture and a grill according to any of Claims 1 to 16 or Claims 18 to 26 mounted over the aperture.
- 25 29. A method for a covering for an opening in an enclosure that houses a fan, the method comprising:  
providing a grill that includes a substantially planar portion and a handle extending out of the planar portion; and  
securing the grill to the housing.
30. A fan grill substantially as hereinbefore described with reference to the accompany drawings.

31. A fan assembly substantially as hereinbefore described with reference to Figure 6.

## ABSTRACT

FAN GRILL

5        The present invention provides a grill 10 for use in electrical equipment comprising a fan. The grill 10 comprises a substantially planar portion 90 that provides protection for (and indeed from) the blades of a fan and a handle 100 that provides means by which the grill may be held. The substantially planar portion 90 may comprise an opening 94 that facilitates stacking of a plurality of like grills 10.

10

Figure 1A






FIG. 1A




FIG. 1B

FIG. 2A





FIG. 2B





**THIS PAGE BLANK (USPTO)**




FIG. 3A




FIG. 3C

**THIS PAGE BLANK (USPTO)**

3/4




FIG. 4




FIG. 5



THIS PAGE BLANK (USPTO)

4/4




FIG. 6

**THIS PAGE BLANK (USPTO)**